

## **PRODUCT SPECIFICATION SHEET**

Item Name : Skintex Cirque

### Specifications :

- Contents: Top - 100% Polyurethane  
Back – 100% Reinforced Pollex
- Width: 54"
- Nominal thickness: .036 gauge
- Repeat: 7.5" Horizontal / 9.5" Vertical
- Roll Length: App. 50yds

### General Characteristics :

- Superior wear resistance: Exceeds 100,000 rubs (ASTM D4157 Wyzenbeek)  
*\*\* Due to delicate taffeta-like surface, gentle care is needed, and scratching of the surface should be avoided. Thus, it is not recommended to use the product for extra heavy duty applications like casino floors, etc.*
- Colorfastness to light (AATCC-16/passes)
- Colorfastness to crocking (AATCC-8/passes)
- Colorfastness to bleach (AATCC-3): Passes 1:10&1:5 dilution test
- Excellent breaking strength (ASTM D5034)
- Excellent tear strength (ASTM D2262)
- Cold crack resistant & mildew resistant backing

### Flammability\* :

- CA Bulletin 117 – Class A
- UFAC/NFPA-260 Class 1
- BIFMA – Class A
- IMO A652 (16) 8.2
- Can be treated to pass ASTM E-84 (Adhered) Class A

\*This term and any other corresponding data refer to typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

### Care & Cleaning :

- Stain Removal: Spot clean with mild soap and warm water solution. Rinse the cleaned area with clean/clear water and dry with air or lint-free cloth

Warranty : Please refer to our Terms of Sales for warranty information.